

# BergaClassic Preprint

WOODFREE UNCOATED PAPER

BergaClassic Preprint is a woodfree uncoated paper for offset printing presses and subsequent personalization in laser printers.

- Designed for multiple needs: from constat forms to A4 letterheads
- Good runnability in converting, laser, inkjet, plotter, automatic inserting
- Good printability in 3/4 colour printing

## TYPICAL END USES

Letterheads  
Direct mail  
Technical manuals  
Statements  
Invoices

## PRINTING METHODS

UV-Offset  
Cold Set Web Offset  
Plain Paper Copiers  
Inkjet (dye)

## CONVERTING

Reel-to-A4  
Reel-to-reel  
Reel-to-fanfold

## POST PRINTING PROCESS

Laser  
Automatic inserting  
OCR  
Plotter

## TECHNICAL SPECIFICATIONS (target values)

Substance		g/m <sup>2</sup>	70	75	80	90	100	115
Brightness	D 65/10°	%	109	109	109	109	109	109
Whiteness	CIE	%	163	163	163	163	163	163
Opacity	ISO 2471	%	91	92	94	95	96	97
Bulk	ISO 534	cm <sup>3</sup> /g	1.30	1.30	1.30	1.30	1.30	1.30
Roughness	Bendtsen	ml/min	270	270	270	270	270	270

## REEL SPECIFICATIONS

Cores	Min. width	Max. width	Diameters
70, 76 mm	210 mm	2144 mm	1000, 1200 mm
150 / 152 mm	210 mm	2144 mm	1200 mm

## ENVIRONMENT

Renewable fibre  
Recyclable paper  
Recyclable packaging materials

## CERTIFICATES

ISO 9001  
ISO 14001  
ISO 9706  
OHSAS 18001  
EU Ecolabel license FI/11/002 and SE/011/001  
Nordic Ecolabel license 444 009 and 3044 0044  
FSC® CoC, license code FSC® C015932  
PEFC™ CoC, licence code PEFC/02-31-86

## PRODUCER

Nymölla Mill  
Veitsiluoto Mill

## STORAGE AND HANDLING

- Store the paper in a humidity and temperature controlled area at 50% relative humidity and room temperature between 19°C and 23°C.
- If the paper is stored in non-air conditioned warehouse, it is absolutely necessary to allow a stabilisation period in the print room.
- Open the protective wrapping at the moment of use.